



R10 Specification Clauses

Product "Sentinel" Modern Ogee Gutter System

Manufacturer ARP Ltd

Unit 2, Vitruvius Way Meridian Business Park

Braunstone Leicester LE19 1WA

ph. 0116 289 4400 Web. <u>www.arp-ltd.com</u>

Specification "Sentinel" Modern Ogee Gutter System

Manufactured from Aluminium Alloy 6063 T6 to BS1474: 1972

Size - 200 x 150mm

Finish Mill Finish Aluminium or Polyester Powder Coated to RAL or

3S______(delete where applicable)

Materials to have factory applied Polyester Powder Coat to all significant surfaces

Fitting

(Direct fix) Gutter to be secured via predrilled holes at 750mm centres with 5 x 25mm stainless

steel countersunk screws (dependant on substrate)

Angles to be secured via the two predrilled holes on rear with 5 x 25mm stainless

steel countersunk screws (dependant on substrate)

Outlets to be via the predrilled hole in rear with 5 x 25mm stainless steel

countersunk screws (dependant on substrate)

Expansion gaps of 3-4mm to be left between butt ends

Outlets Outlets to suit ∅63mm or 76mm or 101mm Circular or 63mm or 76mm or 101mm

Square or 101x76mm Rectangular "Colonnade" downpipes (delete

where applicable)

Jointing Joints to be made by applying two beads of Arbosil 1096 Low Modulus Sealant onto

each side of the joint, offer up the Union Connector and secure using M6 x 20mm

aluminium bolts, neoprene washers and nuts Full fitting instructions to be supplied with delivery