

R10 NBS Specification Clauses

- Product** "Trueline" Pressed Secret Fix Wall Coping System
- Manufacturer** ARP Ltd
Unit 2, Vitruvius Way
Meridian Business Park
Braunstone
Leicester
LE19 1WA
ph. 0116 289 4400
Web. www.arp-ltd.com
- Specification** "Trueline" Pressed Secret Fix Wall Coping System
All components & fittings to BS 2997 (EN612) using 1050AH14 grade aluminium sheet
Profile - Horizontal or Vertical or Angled to ___ degree or _____ (Delete where applicable)
Width- _____ (please allow for 30mm each side) or specify "Trueline" Pressed Wall Coping systems suitable for wall with of _____)
Height - Standard or _____ (please specify)
All additional information as outlined in accordance with ARP Reference EQ_____
- Finish** Mill Finish Aluminium or Polyester Powder Coated to RAL_____ or BS_____ (delete where applicable)
Materials to have factory applied Polyester Powder Coat to all significant surfaces
All additional information as outlined in accordance with ARP Reference EQ_____
- Fitting** Ensure all substrates materials are sound and suitable for fixing to.
Damp proof membrane or waterproofing to cover horizontal wall width
Start installation from corners or ends using an additional supplementary or half bracket
Brackets to be set out at one meter intervals. In the instance of uneven wall width ensure that any additional bracket overhang is set to the internal face
Apply two strips of EPDM sealing tape to each bracket
Fix brackets to wall with a minimum of four 5 x 40mm Stainless Steel flat head screw (depending on substrate)
All additional information as outlined in accordance with ARP Reference EQ_____
- Jointing** Joints to be internal or external union (please specify)
Joints to be sealed with a 6mm bead of Arbosil 1096 Low Modulus Silicone Sealant ensuring 3mm gap is left for expansion & fastened by Fixings to be Stainless Steel or "Trueline" Colour Coated Fixings Polyester Powder Coated to RAL_____ or BS_____ (delete where applicable)
All additional information as outlined in accordance with ARP Reference EQ_____
Full fitting instructions to be supplied with delivery